



MPMC-ETH-RJ45 Module

Specifications

Ethernet Characteristics

- Ports: 2 or 4, 10/100BaseTX
- Port routing: front

PMC Expansion Site Connector

- 3.3V and 5V Signaling
- Types 1 and 2, 32 PCI Bus, 66 Mhz Max

Operating System Support

- Windows®
- Linux®
- VxWorks®
- LynxOS®

Power Requirements

- +3.3Volts

Environmental

Standard Temperature Range

- Operating: 0 to +55 °C
- Storage: -40 to +85 °C

Temperature Range

- Operating: -25 to +75 °C
- Storage: -40 to +85 °C

Humidity for both Ranges

- Operating: 5% to 95% non-condensing
- Storage: 5% to 95% non-condensing

Mean Time Between Failure (MTBF)

- 218,000 Hours

PHOTO COMING SOON

The MPMC-ETH-RJ45 Ethernet Module may be configured as a Drop-in Replacement to the following GE-IP® models: PMC677 PMC610 PMC615 PMC3293.

Features

- PCI 66 MHz capable
- Front I/O
- Quad or dual 10/100BaseTX ports
- Full duplex operation in both 10 and 100 Mbit modes
- TCP/UDP checksum off loading
- Fully supports IP Security (IpSec)
- Versions supporting wide operating temperature range available
- RoHS versions available – meet European Union (EU) Restriction of Hazardous Substance Directive (2002/95/EC) current revision

As with all Merlin Embedded DIR products, the MPMC-ETH has the same, or better, functional performance than the product it is replacing. All Merlin Embedded products are backed by a 2-year warranty and 15 years of life-cycle support. The user will not have to take on any obsolescence issues when utilizing Merlin Embedded products.

All trademarks are the property of their respective owner. Please note that Merlin Embedded is not associated with any of the companies for which our products are drop-in replacements.

Merlin Embedded
10415 Willow Ridge Loop
Orlando, FL 32825
(866) 700 7704
www.merlinembedded.com

